

The lightweight low latency image coding standard

Standardized as JPEG XS (ISO/IEC 21122), the new revolutionary coding standard can be applied in every applications for which a perfect image quality, a microsecond latency, with low power and efficient video bandwidth are crucial.

TicoXS is the intoPIX JPEG XS solution for AV over IP, live broadcast production, TVs and mobile devices, AR/VR systems, gaming, automotive (ADAS), wireless systems, cloud & software video applications or digital cinema workflows.


Designed as a solution for (replacing) uncompressed image and video in many devices and applications, it outperforms all popular video codecs offering the world's best lightweight low-latency coding capabilities:

- **PERFECT IMAGE QUALITY FOR BOTH HUMAN & MACHINE VISION**
 - Extensive bit depth support up to 16bit.
 - No degradation over multiple generations of encoding.
 - Fully transparent to uncompressed quality down to 3bpp (= 10:1 for 444 10bit).
 - Visually lossless down to 1.5bpp on media & natural video content (= 20:1 for 444 10bit).
- **BETTER PIXELS WITH COST SAVINGS, BETTER CONNECTIVITY**
 - For storage and connectivity within a device or within a complete workflow or ecosystem.
 - It enables users to perfectly handle much more pixels (HD, 4K,...), higher bit depth, higher frame rates, at the cost of baseband HD or even lower.
- **LOW COMPLEXITY in FPGA, CPU, GPU**
 - Cross-platform capable, JPEG XS offers various levels of parallelism to scale easily. It is the only international coding standard designed with such revolutionary approach.
 - Extremely small in FPGA (low logic & low memory).
 - Highly parallelizable for CPU & GPU.
- **MICROSECOND LATENCY & LOW POWER**
 - Compared to other popular and high complexity codecs, JPEG XS offers microsecond-latency thanks to an innovative line-by-line processing. JPEG XS is also extremely low power. The technology does not need any external memory, it just requires few internal SRAMs to operate.
- **OPTIONAL FLAWLESS IMAGING PROFILE**
 - Quality beyond the operating range of JPEG XS, 20:1 for KVMs, desktop and AVoIP. Discover our new TicoXS FIP.



Where can TicoXS be implemented?

Wherever you need it as hardware IP-core or software!



TV & mobile devices



VR/AR HMD



Wireless 60GHz/5G/Wifi-6




Wired AV over IP



ADAS lot



Cloud processing & storage



**Chip-to-chip
Chip-to-memory**

- Support more pixels (high resolution, bit depth, frame rates, more streams) using existing systems & infrastructures.
- Reduce your internal video bandwidth (and power!) or cost-effectively increase your video buffer and storage capacity.
- Reduce your bandwidth for real-time wired or wireless transmission without affecting the latency and quality.
- Build an efficient hardware & software based ecosystem without using expensive and power consuming processing, bandwidth, latency and storage capacity.



Specifications and implementations

TicoXS ENCODER & DECODER IP cores & SDKs		
IMAGE/VIDEO	Color format	RGB, YCbCr, Monochrome
	Color subsampling	4:4:4, 4:2:2, 4:2:0, 4:0:0 (Monochrome)
	Bit depth	8 / 10 / 12 / 14 / 16 bits per component
	Resolution	Any up to 10240 x 2160 pixels (Even more on request)
	Frame rates	Any (depending on IP-core or FastTicoXS Developer SDK configuration)
CODING	Compliance	JPEG XS standard (ISO/IEC 21122-1 - High/Main / MLS12 profiles) for TicoXS + additional options (such as the Flawless Imaging Processing)
	Quality	Full transparency to uncompressed, down to 3bpp (according to ISO flicker test), Visually lossless down to 1 bpp, depending on type of content
	Rate control	Line-based latency
	Latency	CBR (constant bit rate) operation - Adjustable down to 36:1 (1bpp)
	Proxy mode	Embedded downscaler in decoder available (decode 1/4, 1/16 proxies)

	TicoXS IP cores	FastTicoXS SDK	
IMPLEMENTATION	Platform	Lattice FPGA Crosslink-NX, Certus-NX, Certus-Pro-NX, ECP2M, ECP5	CPU & GPU OS: Windows, Linux, macOS
	Low complexity & fast processing	Small footprint / Low memory (No external DDR) Various configurations	Highly parallelized SDK processing
	Real-time operation	Latency selectable from 2 lines to 15 lines	Latency selectable from 30 lines to 1 frame/field
	Add-on	IPX-SDI-MAP-TX/-RX : XS over SDI IPX-RTP-TX/RX : XS over RTP/2110-22 IPX-MPEG2-TS : XS over TS IPX-AES: AES128 Encryption	FFmpeg patch Nvidia Rivermax integration intoPIX Titanium Streaming SDK

IP core typical configurations

REFERENCE IP CORES	VIDEO FORMATS			
	Max resolution	Max FPS	Color sampling	Bit depth
IPX-TICO-XS-HD-60-444-12 Enc or Dec	1920 x 1080	60	4:2:2 4:4:4	8, 10, 12
IPX-TICO-XS-UHD4K-60-444-12 Enc or Dec	4096 x 2160	60	4:2:2 4:4:4	8, 10, 12

CONTACT INTOPIX FOR YOUR CUSTOM IP CORE & SDK CONFIGURATION

HEADQUARTERS: intoPIX SA
Rue Emile Francqui 9
B-1435 Mont-Saint-Guibert - Belgium
Tel.: +32 10 23 84 70
sales@intopix.com

EUROPE/MIDDLE EAST: sales.emea@intopix.com
CHINA: sales.china@intopix.com
JAPAN: sales.japan@intopix.com
S. KOREA: sales.korea@intopix.com
USA/CANADA: sales.na@intopix.com