


The lightweight low latency image coding standard

Standardized as JPEG XS (ISO/IEC 21122), the new revolutionary coding standard can be applied in every applications for which a perfect image quality, a microsecond latency, with low power and efficient video bandwidth are crucial.


TICO-XS is the intoPIX JPEG XS solution for AV over IP, live broadcast production, TVs and mobile devices, AR/VR systems, gaming, automotive (ADAS), wireless systems, cloud & software video applications or digital cinema workflows.

Designed as a solution for (replacing) uncompressed image and video in many devices and applications, it outperforms all popular video codecs offering the world's best lightweight coding capabilities:



- **PERFECT IMAGE QUALITY FOR BOTH HUMAN & MACHINE VISION**
 - Extensive bit depth support up to 16bit.
 - No degradation over multiple generations of encoding.
 - Fully transparent to uncompressed quality down to 3bpp (= 10:1 for 444 10bit).
 - Visually lossless down to 1.5bpp on media & natural video content (= 20:1 for 444 10bit).
- **BETTER PIXELS WITH COST SAVINGS, BETTER CONNECTIVITY**
 - For storage and connectivity within a device or within a complete workflow or ecosystem.
 - It enables users to perfectly handle much more pixels (HD, 4K, 8K,...), higher bit depth, higher frame rates, at the cost of baseband HD or even lower.
- **LOW COMPLEXITY in FPGA, CPU, GPU**
 - Cross-platform capable, JPEG XS offers various levels of parallelism to scale easily. It is the only international coding standard designed with such revolutionary approach.
 - Extremely small in FPGA (low logic & low memory).
 - Highly parallelizable for CPU & GPU.
- **MICROSECOND LATENCY & LOW POWER**
 - Compared to other popular and high complexity codecs, JPEG XS offers microsecond-latency thanks to an innovative line-by-line processing. JPEG XS is also extremely low power. The technology does not need any external memory, it just requires few internal SRAMs to operate.
- **OPTIONAL INTOPIX FLAWLESS PROCESSING**
 - Quality beyond the operating range of JPEG XS, ideal for KVMs, desktop and AVoIP.

Where can TICO-XS be implemented? Wherever you need it as hardware IP-core or software!



- Support more pixels (high resolution, bit depth, frame rates, more streams) using existing systems & infrastructures.
- Reduce internal video bandwidth (and power!) or cost-effectively increase video buffer and storage capacity.
- Reduce the bandwidth for real-time wired or wireless transmission without affecting the latency and quality.
- Build an efficient hardware & software based ecosystem without using expensive and power consuming processing, bandwidth, latency and storage capacity.



Specifications and implementations

TICO-XS ENCODER & DECODER IP-cores & SDKs

	IMAGE	
	Color format	RGB, YCbCr, Monochrome
	Color subsampling	4:0:0, 4:2:0, 4:2:2, 4:4:4
	Bit depth	8 / 10 / 12 / 14 / 16 bits per component
	Resolution	Any up to 8192 x 4096 pixels [Even more on request]
	Frame rates	Any [dedepending on IP-core or FastTICO-XS Developer SDK configuration]
	CODING	
	Compliance	JPEG XS standard [ISO/IEC 21122-1 - High/Main profiles] for TICO-XS + additional options
	Quality Rate control Latency	Full transparency to uncompressed, down to 3bpp [according to ISO flicker test], visually lossless down to 1bpp, depending on type of content Line-based latency CBR [constant bit rate] operation - Adjustable down to 36:1 [1bpp]
	Proxy mode	Embedded downscaler in decoder available [decode 1/4, 1/16 proxies]

TICO-XS IP-cores

FastTICO-XS SDK

	TICO-XS IP-cores	FastTICO-XS SDK
IMPLEMENTATION	Platform Xilinx FPGA Spartan-6, Spartan-7, Artix-7, Kintex-7, Kintex and Virtex UltraScale and UltraScale Plus, Zynq Families	CPU: AMD GPU OS: Windows, Linux, macOS
	Low complexity & fast processing Small footprint / Low memory (No external DDR) Various configurations	Highly parallelized SDK processing
	Real-time operation Latency selectable from 2 lines to 15 lines	Latency selectable from 30 lines to 1 frame/field

CONTACT INTOPIX FOR YOUR CUSTOM IP-CORE & SDK CONFIGURATION

IP-core typical configurations

REFERENCE IP-CORES	VIDEO FORMATS			
	Max resolution	Max FPS	Color sampling	Bit depth
IPX-TICO-XS-HD-60-444-12 Enc or Dec	1920 x 1080	60	4:2:2 4:4:4	8, 10, 12
IPX-TICO-XS-UHD4K-60-444-12 Enc or Dec	4096 x 2160	60	4:2:2 4:4:4	8, 10, 12
IPX-TICO-XS-UHD8K-60-444-12 Enc or Dec	7680 x 4320	60	4:2:2 4:4:4	8, 10, 12

HEADQUARTERS: intoPIX SA

Rue Emile Francqui 9
B-1435 Mont-Saint-Guibert - Belgium
Tel.: +32 10 23 84 70
sales@intopix.com

CHINA: sales.china@intopix.com

JAPAN: sales.japan@intopix.com

S. KOREA: sales.korea@intopix.com

USA: sales@intopix.com